



Items: 4035 MR Backing: BOPP film

Adhesive: Acrylic water-based

Colours: ART 4030 MR – 4035 MR – 4035 HT MR – 4930 MR – 4935 MR Brown, Transparent, White ART 4030 COL MR Orange, Blue, Yellow, Red, Green ART 4925 HM MR – 4930 HM MR – 4930 SA MR Yellowish, Brown, White

- · Good initial tack
- · Application with automatic machines
- · Very high resistance and tack after application



Material Informations

Code	Quality	Width (mm)	Length (m)
4035 MR	No Noisy	38,45,48, 50	660, 1000

Technical Informations

Support Thickness	Total Thickness	Adhesion to Steel Plate	Tensile Strength	Elongation
32 mμ ± 3%	50 mμ ±6%	230 gr/cm ± 10%	5,0 Kg/cm ± 10%	150% ± 10%

Storage Conditions

- We recommend a storage temperature between 18 and 30 °C.
- The product should not be directly exposed to heat or humidity.
- The product should be conditioned to room temperature before use.

All the above mentioned values in Technical Informations are to be considered as avarage values of our standard production and cannot be taken as product specifications. The products can present a ±2% tolerance in width and length. We recommend all our customers to make sure that the products is acceptable through preliminary test.