



Rubans Adhésifs
DISTRIBUTION PROFESSIONNELLE

Packaging Tapes



Items: 4930 SA MR

Backing: BOPP film

Adhesive: Acrylic water-based

Colours: ART 4030 MR – 4035 MR – 4035 HT MR – 4930 MR – 4935 MR Brown, Transparent, White
ART 4030 COL MR Orange, Blue, Yellow, Red, Green
ART 4925 HM MR – 4930 HM MR – 4930 SA MR Yellowish, Brown, White

- Good initial tack
- Application with automatic machines
- Very high resistance and tack after application



Material Informations

Code	Quality	Width (mm)	Length (m)
4930 SA MR	Noisy	38,45,48, 50	660, 1000

Technical Informations

Support Thickness		Total Thickness		Adhesion to Steel Plate		Tensile Strength		Elongation	
28 mμ	± 3%	50 mμ	± 6%	290 gr/cm	± 10%	4,5 Kg/cm	± 10%	150%	± 10%

Storage Conditions

- We recommend a storage temperature between 18 and 30 °C.
- The product should not be directly exposed to heat or humidity.
- The product should be conditioned to room temperature before use.

All the above mentioned values in Technical Informations are to be considered as average values of our standard production and cannot be taken as product specifications. The products can present a ±2% tolerance in width and length. We recommend all our customers to make sure that the products is acceptable through preliminary test.